

Specification for Speaker		Page	2/10
		Revision No.	1.0
Model No.	KP50170SP1C40-5877	Drawing No.	KFC5877

CONTENTS

1. Scope
2. General
3. Electrical and Acoustic Characteristics.
4. Reliability Test
5. Measurement Block Diagram & Response curve
6. Structure
7. Dimensions
8. Packing
9. Cautions for Use
10. Revision

Specification for Speaker		Page	3/10
		Revision No.	1.0
Model No.	KP50170SP1C40-5877	Drawing No.	KFC5877

1. Scope

This specification is applied to the dynamic speaker which is used all of the electrical acoustic product.

-- compact, rich sound

-- applications: mobile phone, PDA, notebook computer, etc. ..

2. General

2.1 Out-Diameter : $\phi 50$ mm

2.2 Height : 17.5 mm

2.3 Weight : 50 ± 5 g

2.4 Operating Temperature range:

-25 ~+70 °C without loss of function

2.5 Store Temperature range:

-25 ~+70 °C without loss of function

3. Electrical and Acoustic Characteristics.


Test condition : 15 ~ 35 °C, 25% ~ 85% RH, 860~1060 mbar

No	Items	Specification
1	Impedance	8 Ω $\pm 15\%$ (1Vrms at 1KHz)
2	Sound Pressure Level	88 dB ± 3 dB (1W/1M AVG at 0.8,1.0,1.2,1.5 KHz)
3	Resonance Frequency	400 Hz $\pm 20\%$
4	Frequency Range	Fo ~5.0KHz
5	Input Power	Rated 0.5 W / Max. 1.0 W
6	Distortion	<10% Max. at rated power 2kHz
7	Buzz and Rattle	Should not be audible buzzes,rattles when the 2V sine wave signal swept at frequency range.
8	Polarity	When supplied plus D.C. voltage to (+) terminal, the cone diaphragm must move to forward.

Specification for Speaker		Page	4/10
		Revision No.	1.0
Model No.	KP50170SP1C40-5877	Drawing No.	KFC5877

4. Reliability Test

After test(1~7item), the speaker S.P.L . difference shall be within $\pm 3\text{dB}$, and the appearance not exist any change to be harmful to normal operation (e.g. cracks,rusts,damages and especially distortion).

No	Items	Specification
1	High Temperature Test	After being placed in a chamber with $+70\pm 5\text{ }^{\circ}\text{C}$ for 240 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
2	Low Temperature Test	After being placed in a chamber with $-25\pm 5\text{ }^{\circ}\text{C}$ for 240 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
3	Humidity Test	After being placed in a chamber with 40to90%R.H. at $+40\pm 5\text{ }^{\circ}\text{C}$ for 240 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
4	Thermal Shock Test	<p>After being placed in a chamber at $+70\text{ }^{\circ}\text{C}$ for 1 hour, then speaker shall be placed in a chamber at $-25\text{ }^{\circ}\text{C}$ for 1 hour(1 cycle is the below diagram).</p> <p>After 10 above cycles, speaker shall be measured after being placed in natural condition for 1 hour.</p> 
5	Vibration Test	After being applied vibration of amplitude of 1.5mm with 10 to 55Hz band of vibration frequency to each of 3 perpendicular directions for 1 hour, then placed in natural condition for 1 hour, speaker shall be measured.
6	Drop Test	The speaker when mounted in the jig which weight 85g~100g, shall with stand 15 times random drops from a height of 1.5 meter to concrete floor faced with 5mm thick hard wood board and be nothing mechanical damage .
7	Load test	After being applied loading white noise with input power 0.5W(2Vrms.) for 96 hours, then placed in natural condition for 1 hour, speaker shall be measured.
8	Insulation test	When they are measured with DC 100V the insulation resistance between v.c. terminal and frame must be more than 1 MΩ

Specification for Speaker

Page

5/10

Model No.

KP50170SP1C40-5877



Revision No.

1.0

Drawing No.


KFC5877

5. Measurement Block Diagram & Response curve



Specification for Speaker		Page	6/10
		Revision No.	1.0
Model No.	KP50170SP1C40-5877	Drawing No.	KFC5877

6. Structure



8	Back Plate	1	SPCC	
7	Magnet	1	Y30	
6	Frame and Top plate	1	SPCC	
5	Spider	1	silk iron	
4	Voice Coil	1	Cone Paper +Foam edge	
3	waterproof Cap	1	Paper	
2	waterproof Cone	1	Paper	
1	Gasket	1	Paper	
No.	Part Name	Q'ty	Material	Remarks

Specification for Speaker

Page

7/10

Model No.

KP50170SP1C40-5877



Revision No.

1.0

Drawing No.

KFC5877

7. Dimensions



备注：根据客户要求进行丝印。

UNIT : mm
Tolerance : ± 0.2

Specification for Speaker

Page

8/10

Revision No.

1.0


Model No.

KP50170SP1C40-5877


Drawing No.

KFC5877

8. Packing



70pcs



inner-tray:315X315X70mm
2layer/bundle



70pcs/layer
2layer/carton



QTY:140PCS
SIZE:340x340x14CM

NINGBO KEPO ELECTRONICS CO.,LTD
 CUSTOMER : SHARP
 CUSTOMER P/N : RSPA00005FC8P
 QTY : 140 PCS
 Lot No : NKP×(Year)×(Month)×(Date)×(Flow No.)
 MAKER P/N : KP50170SP1C40-5877
 MADE IN CHINA

KEPO CHECKED	
DATE	

标贴内容

Specification for Speaker		Page	9/10
		Revision No.	1.0
Model No.	KP50170SP1C40-5877	Drawing No.	KFC5877

9. Cautions for Use

1. When assemble the speaker, the frame brim must be hold by hand, and no outside force presses on frame, no sharp tool to damage the frame.

2. Speaker must be used under rated power, and the speaker may broken if it is used out of rated power.

3. Speaker must be keep away from water or liquid.

4. Speaker can't be under the high temperature and high humidity.

