

## Triacs

## BT138X series

## GENERAL DESCRIPTION

Glass passivated triacs in a full pack plastic envelope, intended for use in applications requiring high bidirectional transient and blocking voltage capability and high thermal cycling performance. Typical applications include motor control, industrial and domestic lighting, heating and static switching.


## QUICK REFERENCE DATA

| SYMBOL       | PARAMETER                            | MAX.                | MAX.                | MAX.                | UNIT |
|--------------|--------------------------------------|---------------------|---------------------|---------------------|------|
| $V_{DRM}$    | BT138X-<br>BT138X-<br>BT138X-        | 500<br>500F<br>500G | 600<br>600F<br>600G | 800<br>800F<br>800G | V    |
| $I_{T(RMS)}$ | Repetitive peak off-state voltages   | 500                 | 600                 | 800                 |      |
| $I_{TSM}$    | RMS on-state current                 | 12                  | 12                  | 12                  | A    |
|              | Non-repetitive peak on-state current | 95                  | 95                  | 95                  | A    |


## PINNING - SOT186A

| PIN  | DESCRIPTION     |
|------|-----------------|
| 1    | main terminal 1 |
| 2    | main terminal 2 |
| 3    | gate            |
| case | isolated        |

## PIN CONFIGURATION



## SYMBOL



## LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

| SYMBOL                    | PARAMETER   | CONDITIONS   | MIN. | MAX.                     |                          |             | UNIT             |
|---------------------------|---|--|------|--------------------------|--------------------------|-------------|------------------|
|                           |   |  |      | -500<br>500 <sup>1</sup> | -600<br>600 <sup>1</sup> | -800<br>800 |                  |
| $V_{DRM}$                 | Repetitive peak off-state voltages  |  | -    |                          |                          |             | V                |
| $I_{T(RMS)}$<br>$I_{TSM}$ | RMS on-state current<br>Non-repetitive peak on-state current                      | full sine wave; $T_{ns} \leq 56^\circ\text{C}$<br>full sine wave; $T_j = 25^\circ\text{C}$ prior to surge<br>$t = 20\text{ ms}$<br>$t = 16.7\text{ ms}$<br>$t = 10\text{ ms}$<br>$I_{TM} = 20\text{ A}; I_G = 0.2\text{ A};$<br>$dI_G/dt = 0.2\text{ A}/\mu\text{s}$ | -    |                          | 12                       |             | A                |
| $I^2t$<br>$dI_t/dt$       | $I^2t$ for fusing<br>Repetitive rate of rise of on-state current after triggering |  | -    | 95                       |                          |             | A <sup>2</sup> s |
|                           |   |  | -    | 105                      |                          |             | A <sup>2</sup> s |
|                           |   |  | -    | 45                       |                          |             | A <sup>2</sup> s |
| $I_{GM}$                  | Peak gate current   | T2+ G+   | -    | 50                       |                          |             | A/ $\mu$ s       |
| $V_{GM}$                  | Peak gate voltage   | T2+ G-   | -    | 50                       |                          |             | A/ $\mu$ s       |
| $P_{GM}$                  | Peak gate power   | T2- G-   | -    | 50                       |                          |             | A/ $\mu$ s       |
| $P_{G(AV)}$               | Average gate power  | T2- G+   | -    | 10                       |                          |             | A/ $\mu$ s       |
| $T_{stg}$                 | Storage temperature   |  | -    | 2                        |                          |             | A                |
| $T_j$                     | Operating junction temperature  |  | -    | 5                        |                          |             | V                |
|                           |   |  | -    | 5                        |                          |             | W                |
|                           |   |  | -    | 0.5                      |                          |             | W                |
|                           |   |  | -40  | 150                      |                          |             | °C               |
|                           |   |  | -    | 125                      |                          |             | °C               |

<sup>1</sup> Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 15 A/ $\mu$ s.

## Triacs

## BT138X series

**ISOLATION LIMITING VALUE & CHARACTERISTIC** $T_{hs} = 25^\circ C$  unless otherwise specified

| SYMBOL     | PARAMETER  | CONDITIONS   | MIN. | TYP. | MAX. | UNIT |
|------------|--|--|------|------|------|------|
| $V_{isol}$ | R.M.S. isolation voltage from all three terminals to external heatsink | $f = 50-60 \text{ Hz}$ ; sinusoidal waveform;<br>R.H. $\leq 65\%$ ; clean and dustfree | -    |      | 2500 | V    |
| $C_{isol}$ | Capacitance from T2 to external heatsink                               | $f = 1 \text{ MHz}$  | -    | 10   | -    | pF   |

**THERMAL RESISTANCES**

| SYMBOL        | PARAMETER                               | CONDITIONS                                | MIN. | TYP. | MAX. | UNIT |
|---------------|---|---|------|------|------|------|
| $R_{th j-hs}$ | Thermal resistance junction to heatsink | full or half cycle with heatsink compound | -    | -    | 4.0  | K/W  |
| $R_{th j-a}$  | Thermal resistance junction to ambient  | without heatsink compound in free air     | -    | 55   | 5.5  | K/W  |

**STATIC CHARACTERISTICS** $T_j = 25^\circ C$  unless otherwise stated

| SYMBOL            | PARAMETER                                | CONDITIONS  | MIN. | TYP. | MAX. |      | UNIT |
|-------------------|--|---|------|------|------|------|------|
|                   |  |   |      |      | ...F | ...G |      |
| $I_{GT}$          | Gate trigger current                     | $V_D = 12 \text{ V}; I_T = 0.1 \text{ A}$<br>$T2+ G+$<br>$T2+ G-$<br>$T2- G-$<br>$T2- G+$   | -    | 5    | 35   | 25   | mA   |
|                   |  |   | -    | 8    | 35   | 25   | mA   |
|                   |  |   | -    | 10   | 35   | 25   | mA   |
|                   |  |   | -    | 22   | 70   | 70   | mA   |
| $I_L$             | Latching current                         | $V_D = 12 \text{ V}; I_{GT} = 0.1 \text{ A}$<br>$T2+ G+$<br>$T2+ G-$<br>$T2- G-$<br>$T2- G+$  | -    | 7    | 40   | 40   | mA   |
|                   |  |   | -    | 20   | 60   | 60   | mA   |
|                   |  |   | -    | 8    | 40   | 40   | mA   |
|                   |  |   | -    | 10   | 60   | 60   | mA   |
| $I_H$             | Holding current                          | $V_D = 12 \text{ V}; I_{GT} = 0.1 \text{ A}$  | -    | 6    | 30   | 30   | mA   |
|                   |  |   | -    | 30   | 30   | 60   | mA   |
| $V_T$<br>$V_{GT}$ | On-state voltage<br>Gate trigger voltage | $I_T = 15 \text{ A}$<br>$V_D = 12 \text{ V}; I_T = 0.1 \text{ A}$<br>$V_D = 400 \text{ V}; I_T = 0.1 \text{ A};$<br>$T_j = 125^\circ C$ | -    | 1.4  | 1.65 |      | V    |
|                   |  |   | -    | 0.7  | 1.5  |      | V    |
|                   |  |   | 0.25 | 0.4  | -    |      | V    |
| $I_D$             | Off-state leakage current                | $V_D = V_{DRM(max)}$<br>$T_j = 125^\circ C$   | -    | 0.1  | 0.5  |      | mA   |

## Triacs

## BT138X series

**DYNAMIC CHARACTERISTICS** $T_j = 25^\circ\text{C}$  unless otherwise stated

| SYMBOL        | PARAMETER                                      | CONDITIONS   | MIN.       |            |             | TYP. | MAX. | UNIT             |
|---------------|--|--|------------|------------|-------------|------|------|------------------|
| $dV_D/dt$     | Critical rate of rise of off-state voltage     | <b>BT138X-</b><br>$V_{DM} = 67\% V_{DRM(max)}$ ;<br>$T_j = 125^\circ\text{C}$ ; exponential waveform; gate open circuit                        | ...<br>100 | ...F<br>50 | ...G<br>200 | 250  | -    | V/ $\mu\text{s}$ |
| $dV_{com}/dt$ | Critical rate of change of commutating voltage | $V_{DM} = 400 \text{ V}$ ; $T_j = 95^\circ\text{C}$ ;<br>$I_{T(RMS)} = 12 \text{ A}$ ;<br>$dI_{com}/dt = 5.4 \text{ A/ms}$ ; gate open circuit | -          | -          | 10          | 20   | -    | V/ $\mu\text{s}$ |
| $t_{gt}$      | Gate controlled turn-on time                   | $I_{TM} = 16 \text{ A}$ ; $V_D = V_{DRM(max)}$ ;<br>$I_G = 0.1 \text{ A}$ ; $dI_G/dt = 5 \text{ A}/\mu\text{s}$                                | -          | -          | -           | 2    | -    | $\mu\text{s}$    |

## MECHANICAL DATA

*Dimensions in mm*

Net Mass: 2 g




Fig.13. SOT186A; The seating plane is electrically isolated from all terminals.

### Notes

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".