



MICROCIRCUIT DATA SHEET

MNLP2951-X REV 1B1

Original Creation Date: 08/01/95
Last Update Date: 05/19/98
Last Major Revision Date: 11/11/96

ADJUSTABLE MICROPOWER VOLTAGE REGULATORS

General Description

The LP2951 is a micropower voltage regulator with very low dropout voltage (typ. 40 mV at light loads and 380 mV at 100 mA). It is ideally suited for use in battery-powered systems. Furthermore, the quiescent current of the LP2951 increases only slightly in dropout, prolonging battery life.

An attractive feature is an error flag output which warns of a low output voltage, often due to falling battery voltage on the input. It may be used for a power-on reset. A second feature is the logic-compatible shutdown input which enables the regulator to be switched on and off. Also, the part may be pin-strapped for a 5V output or programmed from 1.24V to 29V with an external pair of resistors.

Careful design of the LP2951 has minimized all contributions to the error budget. This includes a tight initial tolerance(0.5% typ.), extremely good load and line regulation (0.05% typ.) and a very low output voltage temperature coefficient, making the part useful as a low-power voltage reference.

Industry Part Number

LP2951

Prime Die

LP2951

NS Part Numbers

LP2951E/883*
LP2951H/883**
LP2951J/883***
LP2951WG/883****

Controlling Document

See Features Page

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

| Subgrp | Description | Temp (°C) |
|--------|---------------------|------------|
| 1 | Static tests at | +25 |
| 2 | Static tests at | +125 |
| 3 | Static tests at | -55 |
| 4 | Dynamic tests at | +25 |
| 5 | Dynamic tests at | +125 |
| 6 | Dynamic tests at | -55 |
| 7 | Functional tests at | +25 |
| 8A | Functional tests at | +125 |
| 8B | Functional tests at | -55 |
| 9 | Switching tests at | +25 |
| 10 | Switching tests at | +125 |
| 11 | Switching tests at | -55 |

Features

- Error flag warns of output dropout.
- Logic-controlled electronic shutdown.
- Output programmable from 1.24 to 29V.
- SMD : 5962-38705M2A*, MGA**, MPA***, MXA****

(Absolute Maximum Ratings)

(Note 1)

| | | |
|---|---|--|
| Power Dissipation | | |
| METAL CAN | 675mW at +25 C | |
| CERDIP | 1.0W at +25 C | |
| LCC | 1.25W at +25 C | |
| CERAMIC SOIC | 1.0W at +25 C | |
| Storage Temperature Range | -65 C to +150 C | |
| Operating Ambient Temperature Range | -55 C to +125 C | |
| Absolute Maximum Junction Temperature | +160 C | |
| Input Supply Voltage | -0.3 to +30V | |
| Feedback Input Voltage (Note 3, 4) | -1.5 to +30V | |
| Shutdown Input Voltage (Note 3) | -0.3 to +30V | |
| Error Comparator Out. Voltage (Note 3) | -0.3 to +30V | |
| Lead Temperature (Soldering, 10 seconds) | 260 C | |
| Thermal Resistance | | |
| Theta _{JA} | | |
| METAL CAN | (Still Air @ 0.5W) 163 C/W (500LF/Min Air flow @ 0.5W) 95 C/W | |
| CERDIP | (Still Air @ 0.5W) 131 C/W (500LF/Min Air flow @ 0.5W) 75 C/W | |
| LCC | (Still Air @ 0.5W) 95 C/W (500LF/Min Air flow @ 0.5W) 66 C/W | |
| CERAMIC SOIC | (Still Air @ 0.5W) 215 C/W (500LF/Min Air flow @ 0.5W) 130 C/W | |
| Theta _{JC} | | |
| METAL CAN | 51 C/W | |
| CERDIP | 21 C/W | |
| LCC | 24 C/W | |
| CERAMIC SOIC | 24 C/W | |
| Package Weight (Typical) | TBD | |
| ESD Rating | 500V | |

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

Note 2: The maximum power dissipation must be derated at elevated temperatures and is dictated by T_{jmax} (maximum junction temperature), Θ_{JA} (package junction to ambient thermal resistance), and TA (ambient temperature). The maximum allowable power dissipation at any temperature is $P_{dmax} = (T_{jmax} - TA)/\Theta_{JA}$ or the number given in the Absolute Maximum Ratings, whichever is lower.

Note 3: May exceed input supply voltage.

Note 4: When used in dual-supply systems where the output terminal uses loads returned to a negative supply, the output voltage should be diode-clamped to ground.

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 DC: Vin = 6V, Il = 100uA, Cl = 1uF, Vout = 5V, Vshutdown = ≤ 0.8V

| SYMBOL | PARAMETER | CONDITIONS | NOTES | PIN-NAME | MIN | MAX | UNIT | SUB-GROUPS |
|--------|----------------------------|--------------------------------|-------|----------|-------|-------|------|------------|
| | Output Voltage | | | | 4.975 | 5.025 | V | 1 |
| | | | | | 4.94 | 5.06 | V | 2, 3 |
| | Line Regulation | 6V ≤ Vin ≤ 30V | | | -5 | 5 | mV | 1 |
| | | Il = 1mA | | | -25 | 25 | mV | 2, 3 |
| | Load Regulation | 100uA ≤ Il ≤ 100mA | | | -5 | 5 | mV | 1 |
| | | 100uA ≤ Il ≤ 100mA | | | -25 | 25 | mV | 2, 3 |
| | Dropout Voltage | Il = 100mA | 1, 2 | | 450 | mV | 1 | |
| | | | | | 600 | mV | 2, 3 | |
| | | | 1, 2 | | 80 | mV | 1 | |
| | | | | | 150 | mV | 2, 3 | |
| | Ground Current | Vout = 15V, Il = 100mA | | | 0 | 15 | mA | 1 |
| | | | | | 0 | 20 | mA | 2, 3 |
| | | Il = 100mA | | | 0 | 12 | mA | 1 |
| | | | | | 0 | 14 | mA | 2, 3 |
| | | | | | 0 | 30 | uA | 1 |
| | | Vin = 6-30V | | | 0 | 50 | uA | 2, 3 |
| | | | | | 0 | 120 | uA | 1 |
| | Quiescent Ground Current | | | | 0 | 140 | uA | 2, 3 |
| | | | | | 0 | 120 | uA | 1 |
| | | Il = 10uA, Vout = 15V | | | 0 | 140 | uA | 2, 3 |
| | | | | | 0 | 120 | uA | 1 |
| | Dropout Ground Current | Vin = 4.5V | | | 0 | 170 | uA | 1 |
| | | | | | 0 | 200 | uA | 2, 3 |
| | Comparator Lower Threshold | | 1, 3 | | 95 | mV | 1 | |
| | | | | | 140 | mV | 2, 3 | |
| | Comparator Upper Threshold | | 1, 3 | | 40 | | mV | 1 |
| | | | | | 25 | | mV | 2, 3 |
| | Thermal Regulation | Vin = 30V, Il = 50mA, T = 2mS | | | -12.5 | 12.5 | mV | 1 |
| | | Vin = 30V, Il = 50mA, T = 10mS | | | -12.5 | 12.5 | mV | 1 |
| | ISC Current Limit | Vout = 0V | | | 0 | 200 | mA | 1 |
| | | | | | 0 | 220 | mA | 2, 3 |

Electrical Characteristics

DC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)
 DC: Vin = 6V, Il = 100uA, Cl = 1uF, Vout = 5V, Vshutdown = ≤ 0.8V

| SYMBOL | PARAMETER | CONDITIONS | NOTES | PIN-NAME | MIN | MAX | UNIT | SUB-GROUPS |
|--------|------------------------------------|-----------------------------------|-------|----------|------|------|---------|------------|
| | Reference Voltage | | | | 1.22 | 1.25 | V | 1 |
| | | | | | 1.20 | 1.26 | V | 2, 3 |
| | Reference Line Regulation | 2.3V ≤ Vin ≤ 30V | | | -1.9 | 1.9 | mV | 1 |
| | | 2.3V ≤ Vin ≤ 30V | | | -10 | 10 | mV | 2, 3 |
| | Reference Output Regulation | Vref ≤ Vout ≤ (Vin-1V), Vin = 30V | | | -1.2 | 1.2 | mV | 1 |
| | | Vref ≤ Vout ≤ (Vin-1V), Vin = 30V | | | -5 | 5 | mV | 2, 3 |
| | Feedback Bias Current | | | | -40 | 40 | nA | 1 |
| | | | | | -60 | 60 | nA | 2, 3 |
| | Comparator Off Leakage | Vo = 30V | | | -1 | 1 | uA | 1 |
| | | | | | -2 | 2 | uA | 2, 3 |
| | Comparator Output Low Voltage | Vin = 4.5V, Iol = 400uA | | | 0 | 250 | mV | 1 |
| | | | | | 0 | 400 | mV | 2, 3 |
| | Shutdown Input Current | Vshutdown = 2.4V | | | 0 | 50 | uA | 1 |
| | | | | | 0 | 100 | uA | 2, 3 |
| | | Vshutdown = 30V | | | 0 | 600 | uA | 1 |
| | | | | | 0 | 750 | uA | 2, 3 |
| | Output Leakage Current in Shutdown | Vshutdown = 1.5V, Vin = 30V | | | -10 | 10 | uA | 1 |
| | | | | | -20 | 20 | uA | 2, 3 |
| | Shutdown Input Logic Voltage | (LOW) | 1 | | 0.6 | V | 1, 2, 3 | |
| | | (HIGH) | | | 2 | V | 1, 2, 3 | |

Note 1: Functional test only.


Note 2: Dropout voltage is defined as the input to output differential at which the output drops 100mV below its nominal values measured at 1V differential. At very low values of programmed output voltage, the minimum input supply voltage of 2V (2.3V over temperature) must be taken into account.


Note 3: Comparator thresholds are expressed in terms of a voltage differential at the Feedback terminal below the nominal reference voltage measured at Vin = 6V. To express these thresholds in terms of output voltage change, multiply by the error amplifier Gain=Vout/Vin=(R1 + R2)R2. For example, at a programmed output voltage of 5V, the error output is guaranteed to go low when the output drops by 95mV X 5V/1.235V = 384mV. Thresholds remain constant as a percent of Vout as Vout is varied, with the dropout warning occurring at typically 5% below nominal, 7.5% guaranteed.


Graphics and Diagrams


| GRAPHICS# | DESCRIPTION |
|-----------|--|
| 05810HRA2 | METAL CAN (H), TO-99, 8LD, .200 DIA P.C. (B/I CKT) |
| 06059HRA2 | CERDIP (J), 8 LEAD (B/I CKT) |
| 06146HRA2 | LCC (E), TYPE C, 20 TERMINAL(B/I CKT) |
| 06341HRA1 | CERPACK (W), 10 LEAD (B/I CKT) |
| E20ARE | LCC (E), TYPE C, 20 TERMINAL(P/P DWG) |
| H08CRF | METAL CAN (H), TO-99, 8LD, .200 DIA P.C. (P/P DWG) |
| J08ARL | CERDIP (J), 8 LEAD (P/P DWG) |
| P000205A | METAL CAN (H), 8 LEAD (PINOUT) |
| P000206A | CERDIP (J), 8 LEAD (PINOUT) |
| P000251B | LCC (E), 20 LEAD (PINOUT) |
| P000374A | CERAMIC SOIC (WG), 10 LEAD (PINOUT) |
| WG10ARC | CERAMIC SOIC (WG), 10 LEAD (P/P DWG) |

See attached graphics following this page.












LP2951H
8 - PIN METAL CAN
CONNECTION DIAGRAM
TOP VIEW
P000205A




LP2951J
8 - LEAD DIP
CONNECTION DIAGRAM
TOP VIEW
P000206A



LP2951E
20 - LEAD LCC
CONNECTION DIAGRAM
TOP VIEW
P000251B



LP2951WG
10 - LEAD CERAMIC SOIC
CONNECTION DIAGRAM
TOP VIEW
P000374A



Revision History

| Rev | ECN # | Rel Date | Originator | Changes |
|------------|--------------|-----------------|-------------------|--|
| 1B1 | M0002864 | 05/19/98 | Barbara Lopez | Update MDS: MNLP2951-X Rev. 1A0 to MNLP2951-X Rev. 1B1. Added WG package to SMD number and NSID. Updated power dissipation to reflect all packages. Updated thermal resistance to reflect all packages. Updated ESD rating. Updated Absolute junction temperature. Added graphics for all packages. Added Package Weights. |

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

LP2951ACMMX-3.0 - <http://www.ti.com/product/lp2951acmmx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CMMX-3.3 - <http://www.ti.com/product/lp2951cmmx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACM-3.0 - <http://www.ti.com/product/lp2951acm-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACSD-3.0 - <http://www.ti.com/product/lp2951acs-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CMX - <http://www.ti.com/product/lp2951cmx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACM-3.3 - <http://www.ti.com/product/lp2951acm-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMM - <http://www.ti.com/product/lp2951acmm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
5962-3870501M2A - <http://www.ti.com/product/5962-3870501m2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMM-3.0 - <http://www.ti.com/product/lp2951acmm-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACSD-3.3 - <http://www.ti.com/product/lp2951acs-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMM-3.3 - <http://www.ti.com/product/lp2951acmm-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
5962-3870501MGA - <http://www.ti.com/product/5962-3870501mga?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMMX - <http://www.ti.com/product/lp2951acmmx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CMMX-3.0 - <http://www.ti.com/product/lp2951cmmx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
5962-3870501MPA - <http://www.ti.com/product/5962-3870501mpa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMMX-3.3 - <http://www.ti.com/product/lp2951acmmx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
5962-3870501S2A - <http://www.ti.com/product/5962-3870501s2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CSDX-3.0 - <http://www.ti.com/product/lp2951csdx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CSDX-3.3 - <http://www.ti.com/product/lp2951csdx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CMX-3.0 - <http://www.ti.com/product/lp2951cmx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CMX-3.3 - <http://www.ti.com/product/lp2951cmx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACSDX - <http://www.ti.com/product/lp2951acsdx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACSDX-3.0 - <http://www.ti.com/product/lp2951acsdx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACMX - <http://www.ti.com/product/lp2951acmx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACN-3.0 - <http://www.ti.com/product/lp2951acn-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CSD-3.3 - <http://www.ti.com/product/lp2951csd-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACN - <http://www.ti.com/product/lp2951acn?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CSD-3.0 - <http://www.ti.com/product/lp2951csd-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951CN - <http://www.ti.com/product/lp2951cn?HQS=TI-null-null-dscatalog-df-pf-null-wwe>
LP2951ACSDX-3.3 - <http://www.ti.com/product/lp2951acsdx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951C MDC - http://www.ti.com/product/lp2951c_mdc?HQS=TI-null-null-dscatalog-df-pf-null-wwe

5962-3870501SPA - <http://www.ti.com/product/5962-3870501spa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951ACMX-3.0 - <http://www.ti.com/product/lp2951acmx-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

5962-3870501MXA - <http://www.ti.com/product/5962-3870501mxa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CN-3.0 - <http://www.ti.com/product/lp2951cn-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CN-3.3 - <http://www.ti.com/product/lp2951cn-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CSD - <http://www.ti.com/product/lp2951csd?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CSDX - <http://www.ti.com/product/lp2951csdx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951C MWC - http://www.ti.com/product/lp2951c_mwc?HQS=TI-null-null-dscatalog-df-pf-null-wwe

LP2951ACN-3.3 - <http://www.ti.com/product/lp2951acn-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CMMX - <http://www.ti.com/product/lp2951cmmx?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951ACSD - <http://www.ti.com/product/lp2951acs?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951C-3.3 MDC - http://www.ti.com/product/lp2951c-3.3_mdc?HQS=TI-null-null-dscatalog-df-pf-null-wwe

5962-3870501BPA - <http://www.ti.com/product/5962-3870501bpa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951ACMX-3.3 - <http://www.ti.com/product/lp2951acmx-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951C-3.3 MWC - http://www.ti.com/product/lp2951c-3.3_mwc?HQS=TI-null-null-dscatalog-df-pf-null-wwe

LP2951CM - <http://www.ti.com/product/lp2951cm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CM-3.0 - <http://www.ti.com/product/lp2951cm-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951ACM - <http://www.ti.com/product/lp2951acm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CM-3.3 - <http://www.ti.com/product/lp2951cm-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CMM - <http://www.ti.com/product/lp2951cmm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CMM-3.0 - <http://www.ti.com/product/lp2951cmm-3.0?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LP2951CMM-3.3 - <http://www.ti.com/product/lp2951cmm-3.3?HQS=TI-null-null-dscatalog-df-pf-null-wwe>